

N71-34035



CASE FILE
COPY

EVALUATION PROGRAM
for
SECONDARY SPACECRAFT CELLS

ACCEPTANCE TESTS
OF
100 AMPERE-HOUR NICKEL-CADMIUM CELLS
MANUFACTURED BY
GULTON INDUSTRIES

prepared for
GODDARD SPACE FLIGHT CENTER
CONTRACT W12,397

QUALITY EVALUATION LABORATORY
NAD CRANE, INDIANA

DEPARTMENT OF THE NAVY
NAVAL AMMUNITION DEPOT
CRANE, INDIANA 47522

IN REPLY REFER TO:

3053-RET :mm
8900

31 AUG 1971


From: Commanding Officer, Naval Ammunition Depot, Crane, Indiana
To: National Aeronautics and Space Administration, Goddard Space
Flight Center (Code 716.2, Mr. T. J. Hennigan), Greenbelt,
Maryland 20771

Subj: Report QE/C 71-283; Evaluation Program for Secondary Spacecraft
Cells; Acceptance Tests of 100.0 Ampere-Hour Nickel-Cadmium
Spacecraft Cells Manufactured by Gulton Industries

Ref: (a) NASA P. O. No. W12,397

Encl: (1) Report QE/C 71-283

1. In compliance with reference (a), enclosure (1) is forwarded for
information and retention.


D. G. MILEY
By direction

Copy to:
Distribution List

NAVAL AMMUNITION DEPOT
QUALITY EVALUATION AND ENGINEERING LABORATORY DEPARTMENT
CRANE, INDIANA 47522

EVALUATION PROGRAM
FOR
SECONDARY SPACECRAFT CELLS

ACCEPTANCE TESTS
OF
GULTON INDUSTRIES
100.0 AMPERE-HOUR
NICKEL-CADMIUM CELLS

QE/C 71-283 20 JULY 1971

PREPARED BY

R. E. Thomas

R. E. THOMAS

PREPARED UNDER THE DIRECTION OF

D. E. Mains

D. E. MAINS

Manager, Space

Satellite Cell Programs Branch

APPROVED BY

D. G. Miley

D. G. MILEY

By direction

Enclosure (1)

REPORT BRIEF
GULTON INDUSTRIES
100.0 AMPERE-HOUR NICKEL-CADMIUM SPACECRAFT CELLS

Ref: (a) NASA, Langley Research Center, P. O. No. L-32,102
(b) Acceptance Test Procedure for Nickel-Cadmium Cells:
NAD 3022-TP 304, Rev A, 14 May 1970

I. TEST ASSIGNMENT BRIEF

A. The purpose of this acceptance test program is to insure that all cells put into the life cycle program are of high quality by the removal of cells found to have electrolyte leakage, internal shorts, low capacity, or inability of any cell to recover its open circuit voltage above 1.200 volts after cell short tests.

B. The 23 cells were purchased by National Aeronautics and Space Administration, Langley Research Center, from Gulton Industries, Metuchen, New Jersey. These cells were rated at 100.0 ampere-hours. Five of these cells were equipped with auxiliary electrodes. Testing on these cells was funded in accordance with reference (a).

II. SUMMARY OF RESULTS

A. The capacity of the 23 cells ranged from 48.3 to 125.0 ah. Ten cells delivered less than rated capacity on one or more of the three capacity checks.

B. Five cells failed to recover to 1.200 volts as established by the procedure for the cell short tests.

C. Electrolyte leakage was not observed for any of the 23 cells.

III. RECOMMENDATIONS

A. From the results of this acceptance test, it was recommended that these 100.0 ampere-hour cells not be placed on life cycling. This recommendation was based on low capacity of 10 cells and on the failure of five cells to meet the specified recovery voltage during the short tests. It was further noted by National Aeronautics and Space Administration, Langley Research Center, that cells of the same lot as those tested at NAD Crane contained excessive carbonates based on their data. Thus it was mutually agreed that the 23 cells be returned to National Aeronautics and Space Administration, Langley Research Center, for carbonate removal by flushing with electrolyte prior to beginning any life cycling tests on these cells.

RESULTS OF ACCEPTANCE TESTS
OF
100.0 AMPERE-HOUR NICKEL-CADMIUM SPACECRAFT CELLS
MANUFACTURED BY
GULTON INDUSTRIES

I. INTRODUCTION

A. On 7 November 1970 acceptance tests were begun on 23 cells manufactured by Gulton Industries, Metuchen, New Jersey. These tests were completed 11 February 1971.

II. TEST CONDITIONS

A. All acceptance tests were performed at an ambient temperature between 23° C and 27° C at existing relative humidity and atmospheric pressure, in accordance with reference (b) and consisted of the following:

1. Phenolphthalein Leak Test.
2. Three Capacity Tests.
3. Two Cell Short Tests.
4. Phenolphthalein Leak Test.
5. Overcharge Test, c/20 rate and c/10 rate.
6. Internal Resistance.
7. Phenolphthalein Leak Test.

III. CELL IDENTIFICATION AND DESCRIPTION

A. The cells were identified by the manufacturer's serial numbers (14 through 53)--not consecutive.

B. The 100.0 ampere-hour cell is rectangular with an average height, width, and length of 7.308, 7.604 and 1.415 inches, respectively. The average weight was 4121.4 grams for cells without auxiliary electrodes and 4162.0 grams for cells with auxiliary electrodes. Figure 1 is a photograph of the Gulton Industries 100.0 ampere-hour cell.

C. The cell containers, and the cell covers are made of stainless steel. Both terminals are insulated from the cell covers by ceramic seals and protrude through the cover as screw type terminals. The positive and negative terminals are on opposite ends of the cell.

IV. RESULTS-- The following data was condensed from Table I. For details on procedure, see Appendix I.

A. The average capacity for the three capacity checks was:

1. Cells without auxiliary electrodes: 112.7, 106.0, and 94.3 ampere-hours respectively.

2. Cells with auxiliary electrodes: 121.3, 115.3 and 108.3 ampere-hours respectively.

3. Ten of the 23 cells delivered less than rated capacity on one or more of the capacity checks. These ten cells had no auxiliary electrodes. The capacities ranged from 48.3 to 125.0 ampere-hours for all 23 cells.

B. The average recovery voltages for the two short tests (see paragraph I.C. of Appendix I for complete description) were:

1. 24-hour open circuit following dead short:

a. Without auxiliary electrodes: 1.227 volts.

b. With auxiliary electrodes: 1.032 volts.

2. Dead Short; c/10 chg. 5 minute; 24-hour open circuit:

a. Without auxiliary electrodes: 1.232 volts.

b. With auxiliary electrodes: 0.565 volts. Five of the 23 cells failed to recover to the 1.200 volts limit on one or both of the short tests.

C. The end-of-overcharge voltage averaged:

1. Cells without auxiliary electrodes: 1.416 volts at c/20 and 1.422 volts at c/10.

2. Cells with auxiliary electrodes: 1.389 volts at c/20 and 1.376 volts at c/10. One cell, without auxiliary electrode (serial number 52), was removed from the c/10 charge due to pressure over the 30 psig limit.

D. The internal resistance averaged:

1. Cells without auxiliary electrodes: 0.570 milliohms.

2. Cells with auxiliary electrodes: 0.964 milliohms. The internal resistance of the third electrodes averaged 5.8 milliohms.

E. The capacity to 1.000 volt following the overcharge averaged:

1. Cells without auxiliary electrode: 116.2 ampere-hour.
2. Cells with auxiliary electrode: 114.3 ampere-hour.

F. There was no evidence of any leakers out of the 23 cells tested.

QE/C 71-283




FIGURE 1

TABLE I
GULTON 100.0 AMPERE-HOURS CELLS
WITHOUT AUXILIARY ELECTRODES

CELL SN	WEIGHT (IN GRAMS)	HEIGHT (INCHES)	LENGTH (INCHES)	WIDTH (INCHES)	CAPACITY CHECKS (AMPERE-HOURS)			CELL SHORT TEST (VOLTS)		OVERCHARGE (VOLTS) c/20	INTERNAL RESISTANCE c/10 (MILLIOHMS)	C/1 DISCHARGE FOLLOWING OVERCHARGE
					1	2	3	1	2			
14	4098.1	7.305	1.423	7.615	121.7	116.7	106.7	1.188	1.240	1.426	0.620	123.3
15	4112.8	7.312	1.425	7.621	115.0	113.3	105.1	1.210	1.243	1.421	0.659	121.7
16	4124.3	7.305	1.413	7.617	111.7	106.7	98.3	1.215	1.244	1.421	0.522	115.0
17	4133.2	7.312	1.421	7.610	121.7	118.3	108.3	1.204	1.241	1.422	0.640	121.7
18	4132.5	7.316	1.419	7.616	125.0	120.0	111.7	1.171	1.241	1.428	0.481	133.3
19	4115.9	7.317	1.411	7.521	111.7	110.0	98.3	1.232	1.214	1.410	0.620	108.3
20	4112.3	7.311	1.413	7.619	111.7	110.0	105.0	1.238	1.230	1.408	0.595	121.7
22	4126.7	7.317	1.412	7.616	110.0	106.7	96.7	1.246	1.214	1.414	0.479	113.3
23	4139.6	7.320	1.411	7.613	111.7	115.0	110.0	1.221	1.212	1.420	0.490	125.0
24	4124.1	7.316	1.422	7.610	105.0	103.5	91.7	1.251	1.229	1.417	0.542	121.7
26	4120.8	7.306	1.411	7.520	113.3	108.3	98.3	1.239	1.241	1.414	0.739	110.0
27	4124.2	7.321	1.411	7.611	111.7	108.3	96.7	1.237	1.238	1.413	0.678	116.7
28	4101.5	7.302	1.411	7.609	111.7	106.7	96.7	1.235	1.237	1.416	0.525	111.7
29	4121.4	7.305	1.417	7.610	113.0	106.7	100.0	1.238	1.243	1.419	0.499	120.0
33	4131.9	7.307	1.416	7.608	116.7	108.3	100.0	1.240	1.241	1.422	0.655	126.7
50	4120.3	7.305	1.406	7.628	105.0	88.3	66.7	1.237	1.220	1.407	0.500	101.7
52	4137.4	7.316	1.422	7.610	106.7	80.0	48.3	1.245	1.229	1.406	0.530	96.7
53	4108.7	7.306	1.411	7.520	108.3	81.7	58.3	1.243	1.227	1.412	0.490	103.3
AVG	4121.4	*	*	*	112.7	106.0	94.3	1.227	1.232	1.416	0.570	116.2

TABLE I (CONT)
GULFON 100.0 AMPERE-HOURS CELLS
WITH AUXILIARY ELECTRODES

CELL SN	WEIGHT (IN GRAMS)	HEIGHT (INCHES)	LENGTH (INCHES)	WIDTH (INCHES)	CAPACITY CHECKS				CELL SHORT TEST				OVERCHARGE (VOLTS)				INTERNAL RESISTANCE (MILLIOHMS)		C/1 DISCHARGE FOLLOWING OVERCHARGE AUX E CAP. VOLT
					1	2	3	3	1	2	2	2	C/20 CELL	AUX E	C/10 CELL	AUX E	CELL	AUX E	
35	4165.8	7.317	1.422	7.600	121.7	.046	113.3	.089	103.3	.065	1.254	1.211	1.387	.303	1.379	.349	0.770	5.6	115.0 .033
38	4170.8	7.305	1.417	7.615	120.0	.021	111.7	0.54	110.0	.121	1.252	0.201	1.383	.307	1.374	.348	1.050	5.9	120.0 .032
39	4158.4	7.306	1.412	7.610	120.0	.017	111.7	.086	100.0	.085	1.250	1.211	1.382	.370	1.371	.483	0.980	6.2	101.7 -.006
40	4161.2	7.304	1.408	7.619	125.0	.021	123.3	.026	116.7	.023	1.203	0.084	1.395	.131	1.376	.276	1.020	5.9	118.3 .022
41	4153.9	7.300	1.412	7.607	120.0	.014	116.7	.015	111.7	.018	0.203	0.119	1.399	.159	1.382	.236	1.000	5.4	116.7 .015
AVG	4162.0	7.308	1.415	7.604	121.3	.024	115.3	.054	108.3	.042	1.032	0.565	1.389	.254	1.376	.388	0.964	5.8	114.3 .019

*Height, length and width data are averaged for all 23 cells.

QE/C 71-283

APPENDIX I

I. TEST PROCEDURE

A. Phenolphthalein Leak Test:

1. The phenolphthalein leak test is a determination of the condition of the welds and ceramic seals on receipt of the cells. This test was performed prior to any other tests, with a phenolphthalein spray indicator solution of one-half of one percent concentration.

B. Capacity Tests:

1. The capacity test is a determination of the cell capacity at the $c/1$ discharge rate, where c is the manufacturer's rated capacity to a cutoff voltage of 1.00 volt per cell. The discharge was made after a 1-hour open circuit period following the 16-hour charge at the $c/10$ rate. A total of three capacity checks was made at this activity. The cells were discharged individually, but were recharged in series.

2. The five cells with auxiliary electrodes were loaded with 5.1 ohm resistors across the auxiliary electrodes. These resistors were installed prior to the start of the capacity checks and remained throughout the test.

C. Cell Short Test:

1. The cell short test is a means of detecting slight shorting conditions which may exist because of imperfections in the insulating materials, or damage to element in handling or assembly.

2. Following completion of the third capacity discharge test, each cell was loaded with a 0.05 ohm, 10 watt resistor, for 8 hours, then dead shorted with bus wire for 16 hours. At the end of 16 hours, the dead short was removed and the cells were placed on open circuit stand for 24 hours. Any cell whose voltage did not recover to 1.200 volts or higher was considered as failing this portion of the acceptance test.

3. Upon completion of (I.C.2) above, the cells were again loaded with 0.05 ohm resistors for 8 hours, and dead shorted with bus wire for 16 hours. At the end of 16 hours, the bus wire was removed and the cells were charged for 5 minutes at the $c/10$ rate. At the end of 5 minutes the cells were placed on open circuit for 24 hours. Any cell whose voltage dropped below 1.200 volts was considered as failing this portion of the acceptance test.

D. Leak Test:

1. The leak test is a means of detecting leakage of a seal or weld. The test was performed before and after the overcharge test sequence to determine the presence of leaks.

2. The cells were placed in a vacuum chamber and exposed to a vacuum of 40 microns of mercury or less for 24 hours. The cells were then removed from the vacuum chamber and sprayed with phenolphthalein. Pink or redish discolorations would indicate leakage.

E. Overcharge Test:

1. The purpose of this test is basically threefold:

a. To determine the degree to which a pack of cells maintain a balanced voltage.

b. To determine the cells capability of reaching a point of chemical equilibrium--oxygen recombination with the negative (cadmium) plate.

c. To test the integrity of the seals as the pressure increases.

2. The overcharge tests were performed to determine the steady state voltage at specified rates. The test specified a series of constant current charges at c/10, c/20 and c/10 for a minimum of 16 hours at each charge rate. The first c/10 rate serves to establish a condition of overcharge.

3. The cells were monitored hourly throughout the test. Charging was to be discontinued on cells which exceeded 1.55 volts, 49° C, or 30 psig.

F. Internal Resistance:

1. Immediately following the overcharge test, the internal resistance was measured across the cell terminals and, where applicable, across the auxiliary electrodes (from auxiliary electrode terminal to negative terminal). These measurements were made with a Hewlett-Packard milliohmmer (Model 4328A)

G. Leak Test:

1. Following the internal resistance measurements, the cells were still in a charged state. The cells were discharged at c/1 to 0.00 volt and shorted prior to the final leak test. The shorted cells were then placed in a vacuum chamber and the procedure described in paragraph I.D.2. was repeated.

DISTRIBUTION LIST

National Aeronautics and Space Administration, Goddard Space Flight Center (Code 761.2, Mr. T. J. Hennigan), Greenbelt, Maryland 20771 (12 copies)

National Aeronautics and Space Administration (Code RNW, Mr. Ernst M. Cohn), Washington, D. C. 20546

National Aeronautics and Space Administration (Code SCC, Mr. A. M. Greg Andrus), Washington, D. C. 20546

National Aeronautics and Space Administration, Scientific and Technical Information Center; Input, P. O. Box 33, College Park, Maryland 20740 (3 copies)

National Aeronautics and Space Administration (Code UT, Dr. E. N. Case), Washington, D. C. 20546

National Aeronautics and Space Administration (Code MTG, Mr. Richard Livingston), Washington, D. C. 20546

National Aeronautics and Space Administration, Goddard Space Flight Center (Code 734, Mr. Joseph Sherfey), Greenbelt, Maryland 20771

National Aeronautics and Space Administration, Goddard Space Flight Center (Code 734, Mr. Gerald Halpert), Greenbelt, Maryland 20771

National Aeronautics and Space Administration, Goddard Space Flight Center (Code 450, Mr. Louis Wilson), Greenbelt, Maryland 20771

National Aeronautics and Space Administration, Langley Research Center (MS-472, Mr. John L. Patterson), Hampton, Virginia 23365

National Aeronautics and Space Administration, Langley Research Center (MS-488, Mr. Jack E. Zanks), Hampton, Virginia 23365

National Aeronautics and Space Administration, Lewis Research Center (MS 302-1, Dr. Louis Rosenblum), 21000 Brookpark Road, Cleveland, Ohio 44135

National Aeronautics and Space Administration, Lewis Research Center (MS 309-1, Mr. Harvey Schwartz), 21000 Brookpark Road, Cleveland, Ohio 44135

National Aeronautics and Space Administration, Lewis Research Center
(MS 309-1, Dr. J. Stewart Fordyce), 21000 Brookpark Road, Cleveland,
Ohio 44135

National Aeronautics and Space Administration, George C. Marshall
Space Flight Center (S&E-ASTR-EP, Mr. Charles B. Graff), Huntsville,
Alabama 35812

National Aeronautics and Space Administration, Manned Spacecraft
Center (EP-5, Mr. W. E. Rice), Houston, Texas 77058

National Aeronautics and Space Administration, Ames Research Center
(M.S. 244-2, PBS, Mr. Jon A. Rubenzer), Moffett Field, California 94035

Jet Propulsion Laboratory (M.S. 198-220, Mr. Daniel Runkle),
4800 Oak Grove Drive, Pasadena, California 91103

Jet Propulsion Laboratory (M.S. 198-220, Mr. Alvin A. Uchiyama),
4800 Oak Grove Drive, Pasadena, California 91103

Jet Propulsion Laboratory (M.S. 198-220, Dr. R. Lutwack),
4800 Oak Grove Drive, Pasadena, California 91103

Commanding General, U. S. Army Electro Technology Lab, Energy
Conversion Research Division (MERDC), Fort Belvoir, Virginia 22060

Commanding General, U. S. Army Electronics R&D Labs (AMSEL-KL-P),
Fort Monmouth, New Jersey 07703

Commanding General, U. S. Army Electronics Command (AMSEL-ME-NMP-TB-2,
Mr. A. Frink), Fort Monmouth, New Jersey 07703

U. S. Army Natick Laboratories, Clothing and Organic Materials
Division (Mr. Leo A. Spano), Natick, Massachusetts 01762

Harry Diamond Laboratories (Mr. Nathan Kaplan), Room 300, Building 92,
Connecticut Ave. & Van Ness Street, N.W., Washington, D. C. 20438

Chief of Naval Research (Code 473, Director, Power Program),
Department of the Navy, Arlington, Virginia 22217

Chief of Naval Research (Code 472, Mr. Harry Fox), Department of
the Navy, Arlington, Virginia 22217

Director, Naval Research Laboratory (Code 6160, Dr. J. C. White),
4555 Overlook Avenue, S.W., Washington, D. C. 20360

Officer In Charge, Annapolis Division, Naval Ship Research &
Development Center (Code A731, Mr. J. H. Harrison), Annapolis,
Maryland 21402

Commander, Naval Air Systems Command (AIR-340C, Mr. Milton Knight),
Department of the Navy, Washington, D. C. 20360

Commander, Naval Ordnance Laboratory, White Oak (Code 232,
Mr. Philip B. Cole), Silver Spring, Maryland 20910

Commander, Naval Ship Engineering Center (Code 6157C, Mr. C. F.
Viglotti), Center Building, Prince George Center, Hyattsville,
Maryland 20782

Commander, Naval Ship Engineering Center (Code 6157D, Mr. Albert
Himy), Center Building, Prince George Center, Hyattsville,
Maryland 20782

Superintendent, Naval Observatory (STIC, Mr. Robert E. Trumbule),
4301 Suitland Road, Suitland, Maryland 20390

Commander, Naval Ship Systems Command (SHIP-03422, Mr. Bernard B.
Rosenbaum), Department of the Navy, Washington, D. C. 20360

Department of the Air Force Headquarters, Aero Propulsion
Laboratory (APIP-1, Mr. James E. Cooper), Wright-Patterson Air
Force Base, Ohio 45433

Air Force Cambridge Research Laboratory (CREC, Mr. Edward Raskind,
Wing F), L. G. Hanscom Field, Bedford, Massachusetts 01731

Rome Air Development Center (Code EMRED, Mr. Frank J. Mollura),
Griffiss Air Force Base, New York 13442

Headquarters, SAMSO (SMTAE, Lt. R. Ballard), Los Angeles Air Force
Station, Los Angeles, California 90045

National Bureau of Standards (Dr. W. J. Hamer), Washington,
D. C. 20234

Director, Defense Documentation Center, Cameron Station, Alexandria,
Virginia 22314 (20 copies)

Aerospace Corporation (Library Acquisition Group), P. O. Box 95085,
Los Angeles, California 90045

American Cyanamid Company (Dr. R. A. Haldeman), 1937 W. Main Street,
Stamford, Connecticut 06902

AMF, Inc. (Mr. R. A. Knight), 689 Hope Street, Stamford,
Connecticut 06902

American University, Chemistry Department (Dr. R. R. Foley),
Massachusetts & Nebraska Avenues, N. W., Washington, D. C. 20016

Atomics International Division, North American Aviation, Inc.
(Dr. H. L. Recht), P. O. Box 309, Canoga Park, California 91304

Autonetics Division, NAR (Mr. R. F. Fogle, GF 18), P. O. Box 4181,
Anaheim, California 92803

Battelle Memorial Institute (Dr. John McCallum), 505 King Avenue,
Columbus, Ohio 43201

Bellcom, Inc. (Mr. J. J. Sakolosky), 955 L'Enfant Plaza, North,
S.W., Washington, D. C. 20024

Bell Telephone Labs, Inc. (Mr. D. O. Feder), Murray Hill,
New Jersey 07974

Dr. Carl Berger, 13401 Kooteray Drive, Santa Ana, California 92705

The Boeing Company (MS 88-06, Mr. Sidney Gross), P. O. Box 3999,
Seattle, Washington 98124

Burgess Battery Division, Gould, Inc. (Mr. M. E. Wilke, Chief
Engineer), Freeport, Illinois 61032

C & D Batteries, Division of Electric Autolite Co. (Dr. Eugene
Willihnganz), 3043 Walton Road, Plymouth Meeting, Pennsylvania 19462

Calvin College (Prof. T. P. Dirkse), 3175 Burton Street, S. E.,
Grand Rapids, Michigan 49506

Catalyst Research Corporation (Mr. F. Tepper), 6308 Blair Hill Lane,
Baltimore, Maryland 21209

Communications Satellite Corp., Comsat Laboratories (Mr. Robert
Strauss), 1835 K Street, N.W., Washington, D. C. 20036

G. & W. H. Corson, Inc. (Dr. L. J. Minnick), Plymouth Meeting,
Pennsylvania 19462

Cubic Corporation (Librarian), 9233 Balboa Avenue, San Diego,
California 92123

Delco-Remy Division, General Motors Corporation (Mr. J. A. Keralla),
2401 Columbus Avenue, Anderson, Indiana 46011

Eagle-Picher Industries, Inc., Couples Department (Mr. E. P.
Broglia), P. O. Box 47, Joplin, Missouri 64801

E. I. du Pont DeNemours & Company, Engineering Materials Laboratory,
Experimental Station (Bldg. 304, Mr. J. M. Williams), Wilmington,
Delaware 19898

ESB, Inc. (Director of Engineering), P. O. Box 11097, Raleigh,
North Carolina 27604

ESB, Inc., Carl F. Norberg Research Center (Dr. Galen Frysinger),
19 West College Avenue, Yardley, Pennsylvania 19067

Electrochimica Corporation (Dr. Morris Eisenberg), 1140 O'Brien
Drive, Menlo Park, California 94025

Electromite Corporation (Mr. R. H. Sparks), 2117 South Anne Street,
Santa Ana, California 92704

Emhart Corporation (Dr. W. P. Cadogan), Box 1620, Hartford,
Connecticut 06102

Energetics Science, Inc. (Dr. H. C. Oswin), 4461 Bronx Boulevard,
New York, New York 10470

Energy Research Corporation (Mr. Martin Klein), 15 Durant Avenue,
Bethel, Connecticut 06801

Dr. Arthur Fleischer, 466 South Center Street, Orange,
New Jersey 07050

General Electric Company, Research and Development Center
(Dr. R. P. Hamlen), P. O. Box 43, Schenectady, New York 12301

General Electric Company, Space Systems (Mr. K. L. Hanson, Room
M-2700), P. O. Box 8555, Philadelphia, Pennsylvania 19101

General Electric Company, Battery Business Section (Mr. P. R. Voyentzie), P. O. Box 114, Gainesville, Florida 32601

General Electric Company (Whitney Library), P. O. Box 8, Schenectady, New York 12301

General Electric (Mr. David F. Schmidt), 777-14th Street, N.W., Washington, D. C. 20005

Globe-Union, Inc. (Mr. John R. Thomas), P. O. Box 591, Milwaukee, Wisconsin 53201

Globe-Union, Inc. (Dr. Eugene Wissman), 5757 North Green Bay Avenue, Milwaukee, Wisconsin 53201

Gould Ionics, Inc. (Dr. J. E. Oxley), P. O. Box 1377, Canoga Park, California 91304

Grumman Aircraft Engineering Corporation, OAO Project (Mr. Steve J. Gaston, Plant 41), Bethpage, Long Island, New York 11714

Gulton Industries, Battery & Power Sources Division, 212 Durham Avenue, Metuchen, New Jersey 08840

Honeywell, Inc., Livingston Electronic Laboratory (Librarian), Montgomeryville, Pennsylvania 18936

Dr. P. L. Howard, Centreville, Maryland 21617

Hughes Aircraft Corporation (M.S. 524, Bldg. 366, Mr. M. E. Ellion), El Segundo, California 90245

ITT Research Institute (Dr. H. T. Francis), 10 West 35th Street, Chicago, Illinois 60616

Idaho State University, Department of Chemistry (Dr. G. Myron Arcand), Pocatello, Idaho 82301

Institute for Defense Analyses (Mr. R. Hamilton), 400 Army-Navy Drive, Arlington, Virginia 22202

Institute for Defense Analyses (Dr. R. Briceland), 400 Army-Navy Drive, Arlington, Virginia 22202

International Nickel Company (Mr. N. A. Matthews), 1000-16th Street, N.W., Washington, D. C. 20036

Johns Hopkins University, Applied Physics Laboratory (Mr. Richard E. Evans), 8621 Georgia Avenue, Silver Spring, Maryland 20910

Leesona Moos Laboratories (Dr. A. Moos), Lake Success Park, Community Drive, Great Neck, New York 11021

Life Systems, Inc. (Dr. Richard A. Wynveen, Pres.), 23715 Mercantile Road, Cleveland, Ohio 44122

Arthur D. Little, Inc. (Dr. James D. Birkett), Acorn Park, Cambridge, Massachusetts 02140

Lockheed Aircraft Corporation (Bldg. 157, Dept. 62-25, Mr. Robert E. Corbett), P. O. Box 504, Sunnyvale, California 94088

Mallory Battery Company (Mr. R. R. Clune), So. Broadway and Sunnyside Lane, Tarrytown, New York 10591

P. R. Mallory and Co., Inc. (Dr. Per Bro), Northwest Industrial Park, Burlington, Massachusetts 01801

P. R. Mallory and Co., Inc. (Library), P. O. Box 1115, Indianapolis, Indiana 46206

Marathon Battery Company (Mr. Lou Belove), Kemble Avenue, Cold Spring, New York 10516

Martin-Marietta Corporation (M.S. 1620, Mr. William B. Collins & M.S. F8845, Mr. M. S. Imamura), P. O. Box 179, Denver, Colorado 80201

Mauchly Associates, Inc. (Dr. John Mauchly), Commerce and Enterprise, Montgomeryville, Pennsylvania 18936

McDonnell Douglas Astronautics Company (MS 17, BBCO, Mr. A. D. Tonelli), 5301 Bolsa Avenue, Huntington Beach, California 92647

McDonnell Douglas Astronautics Company, Headquarters Space Systems Center (Bldg 11-3-12, MS 12, Dr. George Moe), 5301 Bolsa Avenue, Huntington Beach, California 92647

North American Rockwell Corp., Rocketdyne Division (Library), 6633 Canoga Avenue, Canoga Park, California 91304

Philco-Ford Corporation, Power and Control Engineering Department (M.S. R-26, Mr. D. C. Briggs), 3939 Fabian Way, Palo Alto, California 94303

Portable Power Sources Corporation (Mr. Leon Schulman),
166 Pennsylvania Avenue, Mt. Vernon, New York 10552

Power Information Center, University City Science Institute,
Room 2210, 3401 Market Street, Philadelphia, Pennsylvania 19104

Prime Battery Corporation, 15600 Cornet Street, Santa Fe Springs,
California 90670

RAI Research Corporation, 225 Marcus Boulevard, Hauppauge, New
York 11787

RCA Corporation, Astro Electronics Division (Mr. Paul Nekrasov),
P. O. Box 800, Princeton, New Jersey 08540

SAFT Corporation of America (Mr. D. Verrier), 50 Rockefeller Plaza,
New York, New York 10020

Dr. Robert C. Shair, 58 Harman Road, Edison, New Jersey 08817

Southwest Research Institute (Library), P. O. Drawer 28510,
San Antonio, Texas 78228

Spectrolab, Inc. (Dr. Harvey Seiger), 12484 Gladstone Avenue,
Sylmar, California 91342

Stanford Research Institute (Dr. Fritz R. Kalhammer),
19722 Jamboree Boulevard, Irvine, California 92664

Texas Instruments, Inc. (Dr. J. W. Ross), 34 Forest Street,
Attleboro, Massachusetts 02703

TRW Systems, Inc. (Dr. W. R. Scott, M-2/22154), One Space Park,
Redondo Beach, California 90278

TRW Systems, Inc. (Dr. Herbert P. Silverman, R-1/2094), One Space
Park, Redondo Beach, California 90278

TRW, Inc. (Librarian, TIM 3417), 23555 Euclid Avenue, Cleveland,
Ohio 44117

Tyco Laboratories, Inc. (Dr. Jose Giner), Bear Hill, Hickory Drive,
Waltham, Massachusetts 02154

Union Carbide Corporation, Development Laboratory, P. O. Box 6056,
Cleveland, Ohio 44101

Union Carbide Corporation, Consumer Products Division, (Dr. Ralph Brodd), P. O. Box 6116, Cleveland, Ohio 44101

Union Carbide Corporation, Consumer Products Division (Dr. Robert Powers), P. O. Box 6116, Cleveland, Ohio 44101

University of Pennsylvania, Electrochemistry Laboratory
(Prof. John O'M. Bockris), Philadelphia, Pennsylvania 19104

Utah Research and Development Co., Inc. (Mr. William Boyd),
1820 South Industrial Road, Salt Lake City, Utah 84104

Westinghouse Electric Corporation, Research and Development Center
(Dr. C. C. Hein, Contract Admin.), Churchill Borough, Pittsburg,
Pennsylvania 15235

Whittaker Corporation, Power Sources Division (Mr. L. K. White),
3850 Olive Street, Denver, Colorado 80237

Yardney Electric Co. (Mr. P. Deluca and Mr. M. Read), 82 Mechanic
Street, Pawcatuck, Connecticut 02891